




GATEWAY ARCH



DISTANCE:	42 FEET	VOLUME:	25,985 mL
RATIO:	658,00:1	FORWARD:	14,585 mL
DROP BRUSH:	38 FEET	REVERSE:	11,4 mL
TANKS:	CURVE	PUMP:	MULTI



FORWARD LOADS DATA

#	START	STOP	LOADS	MICS	SPEED	DISTANCE	T.OIL
1	2L	2R	4	45	18	0 → 8	6.660
2	10L	10R	5	45	18	8 → 20	4.725
3	11L	11R	1	50	18	20 → 23	950
4	12L	12R	1	50	18	23 → 25	850
5	13L	13R	1	50	18	25 → 28	750
6	14L	14R	1	50	18	28 → 30	650
7	2L	2R	0	50	22	30 → 37	0
8	2L	2R	0	50	26	37 → 42	0

REVERSE LOADS DATA

#	START	STOP	LOADS	MICS	SPEED	DISTANCE	T.OIL
1	13L	13R	2	50	18	38 → 33	1.500
2	12L	12R	2	50	18	33 → 28	1.700
3	11L	11R	2	45	18	28 → 23	1.710
4	10L	10R	2	45	18	23 → 18	1.890
5	9L	9R	5	40	14	18 → 8	4.600
6	2L	2R	0	40	14	8 → 0	0

THIS PATTERN IS DESIGNED FOR:

VARIABLE BUFFER SPEEDS | VARIABLE MICROLITER STREAMS | REVERSE DROP BRUSH
This pattern may require adjustments if using a lane machine that does not have these features

Created Jul 23, 2025 - Rendered for Atlas.



KEGEL PATTERN LIBRARY APP



PATTERNLIBRARY.KEGEL.NET



SCAN QR CODE FOR
MORE PATTERNS ON
KEGEL PATTERN
LIBRARY

